
UNITED
สายไฟ ยูไนเต็ด

VKF 60227 IEC 53 แบบ VKF 300/500 V 70˚C

2 CORES - ORDINARY POLYVINYL CHLORIDE SHEATHED CORD



Construction

1. Conductor : Bunch stranded annealed copper
2. Insulation : Polyvinyl chloride (PVC)
   Colour code : Light Blue, Brown
3. Sheath : Polyvinyl chloride (PVC), Black colour

Reference Standard

TIS 11 Part 5-2553

Application

* Use for connecting portable electric appliance (heavy duty)
* Use for connecting lamp

Classification

Maximum conductor temperature : 70˚C
Rated voltage : 300/500 V
AC test voltage : 2,000 V

No. of core	Conductor: Croos-sectional area mm²	Conductor: Dia. of wires mm (Mix.)	Conductor: Conductor resistance at 20˚C Ω/km (Upper limit)	Thickness of insulation mm	Thickness of sheath mm	Overall diameter: Lower limit mm	Overall diameter: Upper limit mm	Current rating in free air A	Insulation resistance at 70˚C MΩ-km (Min.)	Cable weight kg/km (Approx.)	Standard length m
2	0.75	0.21	26.0	0.6	0.8	3.7 x 6.0	4.5 x 7.2	6	0.011	44	100/C
2	1	0.21	19.5	0.6	0.8	3.9 x 6.2	4.7 x 7.5	10	0.010	52	100/C

C = Packing in coil

UNITED
สายไฟ ยูไนเต็ด

VKF 60227 IEC 53 แบบ VKF 300/500 V 70˚C

สายอ่อนมีเปลือกพอลิไวนิลคลอไรด์ธรรมดา แรงดันไฟฟ้ากำหนด 300/500 โวลต์ อุณหภูมิ 70˚C มอก.11 เล่ม 5-2553

Product	Core	Size	Baht / Meter
IEC 53 VKF	2	0.75	17.30
		1	22.30

***ราคาอาจมีการเปลี่ยนแปลง โดยไม่ต้องแจ้งให้ทราบล่วงหน้า**